



BILIGHT HORIZONTAL

GCH 150 44 30 B12 TSRC



TIN Code	306158
Model	BiLight 150 H
Real Volume	141 L
Height	0.440 m
Width	1.325 m
Depth	0.467 m
Rated power	3000 W
Mounting	Horizontal
Heating time Δt 45K (15 - 60°C)	2:27 h:min



Annual consumption of electricity AEC	2765 kWh
Energy class	C
Diameter	440 mm
V40	190 L
T _{out of the box}	60 °C
MAX40	229 L
Design	Yes



In BiLight horizontal models* we are using the innovative TESI AquaMore Technology: REVOLUTIONARY SOLUTION FOR MORE HOT WATER

It provides up to 40%* more hot water for TESI BiLight horizontal models, compared to TESI BiLight horizontal models without this technology.

With this innovative technology, a horizontal TESI water heater delivers a comparable quantity of hot water as a vertical one.

- INSUTECH - an in-house TESI technology for highly efficient insulation and extremely low heat losses
- Bi light indication for easy and fast recognition of the work modes
- Electric on/off switch
- Freeze protection
- Glass-ceramic coating for corrosion protection
- Plasma-arc welding of the water tank for extended useful life

*For TESI BiLight Horizontal models with AquaMore Technology compared to TESI BiLight Horizontal models without this technology.

*BiLight Horizontal 50 L is not with TESI AquaMore Technology.