



BELLISLIMO LITE DRY

GCR 80 27 12D E32 EC



TIN Code	306087
Range	80
Model	BelliSlimo Lite Dry 80
Real Volume	65 L
Height	1.053 m
Width	0.490 m
Depth	0.280 m



Rated power	1200/1200 W
Mounting	Reversible
Heating time Δt 45K (15 - 60°C)	2:49 h:min
Annual consumption of electricity AEC	1317 kWh
Energy class	B
Load profile	M
V40	140/107 L
T _{out} of the box	80/80 °C
MAX40	140/107 L
Design	Yes



INNOVATIVE AND CONVENIENCE FEATURES

LIME SCALE PROTECTION AND QUIET OPERATION ensured by 2 dual dry heating elements

EASY AND INTUITIVE touch control panel

BUILT FOR SPACE SAVING with elegant flat slim silhouette

REVERSIBLE: can be installed vertically or horizontally

ENERGY SAVING FEATURES

UP TO 18% ELECTRICITY SAVINGS on a weekly basis by ECO SMART self-learning regime

SECURITY AND LONG PRODUCT LIFE FEATURES

HIGH RELIABILITY AND SAFETY of the heating process by precise CAPILLARY THERMOSTAT

RELIABLE CORROSION PROTECTION due to CRYSTALTECH enamel coating of the water tank

LONGER LIFE of the water tank ensured by Magnesium anode

HIGH TEMPERATURE AND PRESSURE RESISTANCE with stainless steel hot water pipe

DURABLE BOND between the edges of the cylinder by PLASMA WELDING

HYGIENIC CERTIFICATE

PRESSURE RELIEF VALVE to prevent excess pressure build-up

ANTI-FREEZE protection

SELF-DIAGNOSTICS SYSTEM helps identify potential device issues

BelliSlimo Lite Dry – a new model flat electric water heater in the BelliSlimo series with two dual dry heating



elements, specifically developed for regions with hard or aggressive water.